

GNCI MRM X1100 Product Specifications	
Interfaces	1x High power USB 2.0 host interface, 5V/1A 1x RJ45 Ethernet 10/100Mb auto-sense, MDI/MDI-X 1x Micro-USB power jack
Supported Modems	Sierra Wireless, Novatel Wireless, Huawei, ZTE, Pantech, LG, Sony Ericsson, Nokia, Option, others ^{1 2}
Battery Backup	Built-in 1800mAh Li-Ion battery acts as UPS (Uninterruptible Power Source) Runtime on battery: 3-4 hours under normal conditions
Throughput	Max. 100 Mbit/s - limited by Ethernet port
Software	IP Pass-through, NAT, DHCP, Static IP, DNS, HTTP, HTTPS, SSH, Telnet, Access Control, Routing, Secondary Ethernet IP, DDNS, RADIUS ³ , NTP, Syslog, Remote Syslog, Failsafe config, WWAN Traffic Counter
Monitoring	SNMP with custom MIB for WWAN network status monitoring ³
Power	DC 5V/1A from existing USB port or optional AC adapter
Dimensions	9.5cm x 3.5cm x 1.4cm (3.7" x 1.4" x 0.6")
Mounting Options	Optional mounting bracket available
Certification	FCC, CE, RoHS
Operating Environment	Temperature: 0°C to 40°C (30°F to 105°F) Humidity: 5% to 90% non-condensing
¹ GNCI adds support for new modems - contact us for an up-to-date list of specific supported models. ² All trademarks and registered trademarks are the property of their respective owners. ³ Software license required for SNMP/RADIUS feature set.	



Global Net Commerce, Inc.
Secure In Wireless • Solid In Solutions

Global Net Commerce, Inc. (GNCI)
711 West 17th Street, Unit G-9
Costa Mesa, CA 92627

Phone: 949-515-1960 Web: www.gnciwireless.com
Fax: 949-515-2970 Email: info@gnciwireless.com